

Washer Ultra Dry

WASCOMAT WUD SERIES

Combining world-class reliability with innovative features and programmability, **Wascomat washers are designed to work as a system with Wascomat dryers.** The washer initiates the drying process which means, the higher the G-force, the more water is extracted from the laundry. This speeds up the drying process, saving energy, time, and money.



Wash and dry in less than an hour with Wascomat WUD Washers. You will also save energy and up to 50% on water – automatically.

- Automatic Savings (AS) determines the exact load weight and adds precisely the right amount of water for significant savings
- Compass Pro lets you control important functions such as exact water levels, wash times and number of rinses – with a simple turn of the dial
- Robust door handle – durable in any environment
- Door unlocks immediately at the end of final cycle – no delays
- Unique 4-compartment supply dispenser
- Extended machine life with Super Balance
- Sanitizing Rinse generates customer loyalty, gives customers peace of mind
- Text messaging and voice guidance features (optional)
- Innovative LaundryPulse and LaundryPay (optional)
- Interchangeable parts from one machine size to another

Features and Benefits

Wascomat Compass Pro provides the ultimate in flexibility:

- Create fully customized wash programs to lower costs and meet customer demands for your specific market
- Cycle upgrade options increase store revenue and boost customer satisfaction
- Display wash program information in multiple languages
- Real-time clock for happy hour, promotional pricing

Eco-Friendly Solutions

Wascomat products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

High Speed Extraction

The perfect balance of speed, performance, and BIG savings. High-speed spin removes more water for faster drying times and better wash performance.

Easy Installation


Soft-mount technology allows WUD Series washers to be installed on wood floors, upper floors, and over basements.

LaundryPay Transforms the Laundry Experience for Your Customers

Attract new customers and build loyalty by providing the most convenient laundry service available. With our LaundryPay App, your customers can pay through their smartphone, view machine availability, and receive a notification when their wash cycle is complete.

Ultimate Control with LaundryPulse


Remotely monitor, manage, and control your business – from anywhere at any time with Laundry Pulse. Get instant service alerts, performance data, real-time revenue and utilization reports, diagnostic info, and more delivered right to your phone. You can even remotely adjust pricing and create promotional campaigns to generate business on slower days.




Wascomat "WUD" Series Washers	WUD718		WUD725		WUD730		WUD745		WUD760		WUD775	
Capacity (lb/kg)	18	8	25	11	30	14	45	20	60	27	75	33
Width (in/mm)	28 3/8	720	32 11/16	830	35 13/16	910	38 3/16	970	40 3/16	1020	40 3/16	1020
Depth (overall) (in/mm)	28 3/8	721	29 13/16	757	32 5/16	821	37 1/4	947	39	990	44 3/4	1134
Height (in/mm)	44 9/16	1132	47 11/16	1212	52 3/4	1340	56	1426	57 1/2	1462	57 1/2	1462
Height to bottom of door (in/mm)	14	355	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	17 1/8	435	17 1/8	435	17 1/8	435
Cylinder volume (ft ³ /l)	3.6	75	3.7	105	4.6	130	6.4	180	8.5	240	10.6	300
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/16	103	4 1/16	103	3 15/16	100	3 15/16	100	3 15/16	100
Extract (rpm/G-Force)	1098 / 350		1025 / 350		980 / 350		930 / 350		890 / 350		820 / 300	
Dynamic floor load (lb/kN)	417 +/- 110	1.9 +/- 0.5	560 +/- 112	2.5 +/- 0.5	703 +/- 114	3.1 +/- 0.5	944 +/- 221	4.2 +/- 1	1158 +/- 221	5.2 +/- 1	1387 +/- 277	5.2 +/- 1.2
Dynamic frequency (Hz)	18.3		17.1		16.3		15.5		14.8		13.7	
Noise level (dBA) in extraction	<75		<78		<79		<85		<85		<84	
Crated width - (in/mm)	29 15/16	760	33 7/8	860	37 13/16	960	40 3/16	1020	41 5/16	1050	41 5/16	1050
Crated depth - (in/mm)	32 1/2	825	34 1/4	870	37 13/16	960	41 5/16	1050	42 15/16	1090	47 1/4	1200
Crated height - (in/mm)	50	1270	53 1/8	1350	58 11/16	1490	61 13/16	1570	63	1600	63	1600
Crated weight (lb/kg)	373	170	474	216	611	278	816	371	974	443	1274	580
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.7 / 3.4 / 15		1.1 / 5.3 / 15		1.5 / 7.2 / 15		2.5 / 12.0 / 15		2.7 / 13.0 / 20		3.0 / 14.4 / 20	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1							
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.8 / 6.7 / 15		1.2 / 10 / 15		1.7 / 14.2 / 20				n/a			
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	8	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	9.6	36	10.7	41	16.8	64	20.3	77	30.2	115	38.4	145
Modified Energy Factor	2.7		2.7		2.6		2.4		2.4		2.4	
Water Factor (Gal per cycle/drum volume)	3.9		3.4		4.0		3.9		3.9		3.9	
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.												

Contact us today to learn more about our new products and technologies.

Front Panel Options

 **White**
Standard on 18 & 25lb Models

 **Brushed Stainless Steel**
Standard on 30-75lb Models
Optional Upgrade on 18 & 25lb Models



Wascomat WUD Series 30-75lb. Model Design and Construction.

 **LaundryLux**
Distribution

laundryluxdistribution.com

Laundrylux

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

